

MATERIAL SAFETY DATA SHEET

I - PRODUCT INFORMATION

Company Name: RBR Productions, Inc./Isabel Cristina	In NJ: (201) 498-1044
Address: PO Box 3599, Teaneck, NJ 07666	Outside NJ: (800) 247-4130
Product Name: Let's Hold Medium Weight Adhesive	Poison Control Center: (800) 222-1222
Synonyms: Nail Glue	Product No.: LH MEDWT CP

II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS (CAS#)	OSHA PEL	ACGIH TLV	OTHER LIMITS	% OPTION
Common Names				
Ethyl-2-Cyanoacrylate (7085-85-0)	NE	NE	2ppm TWA	60-100
Hydroquinone* (123-31-9)	2mg/m3	2mg/m3		0-1
Poly (Methyl Methacrylate) (9011-14-7)	NE	NE		10-30

* This ingredient is subject to the reporting requirements of Section 313 of Title III (SARA) and 40 CFR 372.

III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 149 F	Specific Gravity H2O=1: 1.05
Vapor Density (Air=1): nil-NE	Melting Point: NE
Vapor Pressure (mm Hg):1 @ 20 C	Evaporation Rate (Butyl Acetate=1): nil-NE

Solubility in water: Insoluble, material reacts to hardened mass for non-hazardous waste.

Appearance & Odor: Transparent water-white to straw colored liquid with stimulative odor.

IV - FIRE AND EXPLOSION

Flash Point (Method Used): 176 F (TCC)	Flammable Limits: LEL: NE UEL: NE
--	-----------------------------------

Extinguishing Media: Flush with large amounts of water or dry chemical extinguisher.

Special Fire Fighting Procedures: Fumes may be irritating if not burning and require air supply with goggles while applying large amounts of water or dry chemical extinguisher.

Unusual Fire and Explosion Hazards: None. Combustible requiring the above procedures.

V - REACTIVITY DATA

Stability: _____ Unstable XX Stable

Conditions to avoid: Excessive heat above 176 F, moisture and alkalines.

Stable up to 122 F. Store in a cool, dry place.

Incompatibility: Polymerized by water, alcohol, amines, alkaline materials, and direct UV.

Hazardous Decomposition Products: Combustible by-products of carbon monoxide/dioxide.

Hazardous Polymerization: May not occur.

VI - HEALTH HAZARD DATA

Routes of entry:	Inhalation YES	Skin NO	Ingestion LD50=12.2cc/kg (mice)
------------------	-------------------	------------	---------------------------------------

(continued on page 2)

VI - HEALTH HAZARD DATA (cont.)

Health Hazards (Acute and Chronic):

Acute: Irritates eyes, mucous membranes.

Chronic: No residual effects of acute properties.

Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No

Signs and Symptoms of Exposure and First Aid Procedures:

Eye Contact: Tearing from eye irritation. Remove to fresh air. Flush areas of contact with water. Adhesive will disassociate from eye/eyelids over time, usually within several hours. Temporary weeping of eyes/double vision may be experienced until clearance is achieved.

Skin Contact: Immerse bonded areas in warm, soapy water. Peel or roll skin apart. Remove cured adhesive with several applications of warm, soapy water. Prolonged or repeated contact may cause dermatitis in sensitive individuals.

Inhalation: Irritation of mucous membranes/coughing. Remove to fresh air. Prolonged or repeated exposure may produce allergic reactions with asthma-like symptoms in sensitive individuals.

Ingestion: Lips may become stuck together: apply copious amounts of warm water & encourage wetting/pressure from saliva inside mouth. Peel or roll (do not pull) lips apart. It is almost impossible to swallow cyanoacrylate as adhesive solidifies upon contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days, avoid swallowing adhesive after detachment.

Medical Conditions Generally Aggravated by Exposure: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure.

VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled: Polymerize with water. Solid material may be scraped from surface.

Waste Disposal Method: Incinerate solid combustible waste or dump as chemical waste according to local, state, and federal regulations.

Precautions to be Taken in Handling and Storing: Avoid moisture, direct UV-sunlight, and do not store above 25 C. Keep containers closed tightly when not in use. Ideal storage: 5-10 C.

Other Precautions: Avoid breathing vapor, contact with eyes/skin. Do not store at -5 C, which freezes product to useless state. Product not damaged by freezing.

VIII - CONTROL MEASURES

Respiratory Protection (specify Type): A NIOSH-approved organic vapor canister may be used to maintain vapor concentration below TLV.

Ventilation: Local exhaust: to maintain vapor concentration below TLV.

Mechanical (General): Large amounts used to 2ppm.

Protective Clothing or Equipment: Safety glasses with side shield. Vinyl (polyethylene) non-sticking gloves, rubber apron to protect clothing.

Work/Hygienic Practices: Soap and water helps remove adhesive from skin.

NE = Not Established.

The data contained herein is based upon information that RBR Productions, Inc. believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to insure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material, or the results to be obtained from the use thereof.